

Mobile Manipulation in der Telerobotik

Angelika Peer, Thomas Schauß, Ulrich Unterhinninghofen, Martin Buss

`angelika.peer@tum.de`
`schauss@tum.de`
`ulrich.unterhinninghofen@tum.de`
`mb@tum.de`

*Lehrstuhl für Steuerungs- und Regelungstechnik
Technische Universität München*

Motivation

Autonomous robots

- Favorable for many tasks (compared to humans)
- Limited cognition → restrictions on environment

→ **Teleoperation**

Human scale environments

- Workspace of human scale required
- Often also locomotion required


→ **Wide-Area Teleoperation**

Natural sense of locomotion

- Beneficial for navigational skills and feeling of immersion
- Exoskeletons very fatigueing, joystick/foot pedal unintuitive

→ **Coupling of a mobile haptic interface with a mobile teleoperator**

Motivation



Related Work

Control of Mobile Haptic Interfaces


- Development [Nitzsche 2003], [Pascale et al, 2006], [Formaglio 2008]

Wide-area teleoperation

- One arm only, direct mapping only [Nitzsche 2004]
- Bimanual, direct mapping only [Buss 2008]



[Nitzsche, 2003]



[Pascale et al, 2006]

Outline

Coupling schemes

Optimization of base position

Experimental Results

- Manipulation while standing still
- Locomotion
- Video

Conclusion

Outline

Coupling schemes

Optimization of base position


Experimental Results

- Manipulation while standing still
- Locomotion
- Video

Conclusion

Coupling of End-Effectors Only

Coupling scheme



Disadvantage


- No direct mapping between operator locomotion and motion of TOP base

Advantage

- No tracking of human operator necessary

Coupling of Body and End-Effectors

Coupling scheme



Disadvantage

- Tracking of human operator required

Advantage

- Direct mapping between operator locomotion and motion of TOP base

Outline

Coupling schemes

Optimization of base position

Experimental Results


- Manipulation while standing still
- Locomotion
- Video

Conclusion

Mobile Haptic Interface

Design objectives:

- Simultaneous locomotion and manipulation in large remote environments
- Manipulations in 6 DOF
- High interaction forces
- Avoid operator fatigue
- Decoupling of translational and rotational movements



Manipulability Measure

Manipulability


- Velocity manipulability
- Only planar degrees of freedom relevant

Jacobian

$$\begin{aligned} J &= \begin{pmatrix} \frac{\delta x}{\delta q_2} & \frac{\delta x}{\delta q_3} \\ \frac{\delta y}{\delta q_2} & \frac{\delta y}{\delta q_3} \end{pmatrix} \\ &= \begin{pmatrix} -l_2 \sin(q_2) - l_3 \sin(q_2 + q_3) & -l_3 \sin(q_2 + q_3) \\ l_2 \cos(q_2) + l_3 \cos(q_2 + q_3) & l_3 \cos(q_2 + q_3) \end{pmatrix} \end{aligned}$$

Smallest Singular Value

- Maximum speed in arbitrary direction
- Circles of maximum manipulability with radius r_{opt}



Maximizing Manipulability


Optimal Position

- Maximum manipulability
- End-effectors on circle with r_{opt}

Geometric Solution

$$\mathbf{n} = \frac{\mathbf{d}}{\|\mathbf{d}\|} \times \mathbf{e}_z$$

$$n_{opt} = \sqrt{r_{opt}^2 - \left(\frac{\|\mathbf{d}\| - d_P}{2} \right)^2} + n_P$$





Including Human Arm Workspace in Optimization Strategy

Motivation

- Limited repositioning speed of mobile base
- Suboptimal position in transient phases

Extension

- Consider human arm workspace



Advantages

- Faster arm motions possible
- Less repositioning efforts

Disadvantage

- Tracking of operator position required

Outline

Coupling schemes

Optimization of base position


Experimental Results

- Manipulation while standing still
- Locomotion
- Videos


Conclusion

Experimental Setup

Mobile Haptic Interface (MHI)




Mobile Teleoperator (TOP)




Manipulation While Standing Still

Coupling of End-Effectors Only



Coupling of Body and End-Effectors




- No tracking between operator body and teleoperator base
- + End-effectors maintain same distance from body


- + Tracking between operator body and teleoperator base
- End-effectors reach workspace boundaries

Locomotion

Coupling of End-Effectors Only




Coupling of Body and End-Effectors



- No tracking between operator body and teleoperator base
- + End-effectors maintain same distance from body

- + Tracking between operator body and teleoperator base
- End-effectors reach workspace boundaries

Video



Video



HRP-2 Teleoperation and Cooperation with On-Site Human

Thomas Schauß
Carolina Weber
Angelika Peer
Martin Buss

Paul Evrard
Nicolas Mansard
Olivier Stasse
Abderrahmane Kheddar



Conclusion

Wide-area teleoperation


- Exoskeletons very fatigueing, joystick/foot pedal unintuitive
→ Mobile haptic interface coupled with mobile teleoperator

Two coupling schemes for wide-area teleoperation:

- Coupling of end-effectors only
 - Optimization of base positions by using local optimization strategies
 - No tracking of operator required
 - Enhances ease of use
- Coupling of body and end-effectors
 - Direct mapping of operator locomotion to base position
 - Tracking of operator required
 - Visual cues more closely resemble proprioception



Haptic Interaction

High-Fidelity Telepresence and Teleaction



Advanced teleoperation controllers

Single and multi-user scenarios





Haptic Human-Robot Interaction




Analysis of human-human interaction


Synthesis of interactive robotic systems




Design and control of haptic interfaces




Intention recognition



Adaptation



Joint decision making





Acknowledgements

This work is supported in part by the German Research Foundation (DFG) within the collaborative research center SFB453 “High-Fidelity Telepresence and Teleaction” and in part by the European Commission under Contract FP6 034002 ROBOT@CWE. For the content of this paper the authors are solely responsible, it does not necessarily represent the opinion of the European Community.

References

- [Buss 2009] Buss M, Peer A, Schauß T, Stefanov N, Unterhinninghofen U, Behrendt S, Leupold J, Durkovic M, and Sarkis M: Development of a Multi-modal Multi-user Telepresence and Teleaction System, The International Journal of Robotics Research 2009
- [Formaglio 2008] Formaglio A, Prattichizzo D, Barbagli F, Giannitrapani A: Dynamic performance of mobile haptic interface, IEEE Transactions on Robotics, Vol. 24, 2008
- [Künzler 2005] Künzler U, Runde C: Kinesthetic haptics integration into large-scale virtual environments. World Haptics 2005.
- [Nitzsche 2003] Nitzsche N, Hanebeck U, Schmidt G: Design issues of mobile haptic interfaces. Journal of Robotic Systems Vol. 20, 2003
- [Nitzsche 2004] Nitzsche N, Schmidt G: A mobile haptic interface mastering a mobile teleoperator. IEEE/RSJ IROS 2004
- [Peer 2007] Peer A, Komoguchi Y, Buss M: Towards a mobile haptic interface for bimanual manipulations. IEEE/RSJ IROS 2007
- [Schauß 2009] Schauß T, Unterhinninghofen U, Buss M: Unlimited Workspace – Coupling a Mobile Haptic Interface with a Mobile Teleoperator, HCRS 2009
- [Stanczyk 2006] Stanczyk B: Developement and Control of an Anthropomorphic Teleoperator. PhD thesis, Technische Universität München, Lehrstuhl für Steuerungs und Regelungstechnik, 2006
- [Unterhinninghofen 2008] Unterhinninghofen U, Schauß T, Buss M: Control of a mobile haptic interface. IEEE ICRA 2008

