

# Knowledge Representation and Semantic Technologies – 19/7/2016

LAST NAME: \_\_\_\_\_  
FIRST NAME: \_\_\_\_\_  
ID (MATRICOLA): \_\_\_\_\_

Autorizzo la pubblicazione del mio voto di questo esame sul sito web <http://www.dis.uniroma1.it/~rosati/gd>, secondo quanto prevede il decreto legislativo 196/2003 (codice in materia di protezione dei dati personali) che dichiaro di conoscere. In fede,  
\_\_\_\_\_

**Exercise 1** Given the following  $\mathcal{ALC}$  TBox:

$$\begin{aligned} A &\sqsubseteq B \\ A &\sqsubseteq C \\ B &\sqsubseteq \exists R.\neg D \\ C &\sqsubseteq \exists R.D \\ E &\sqsubseteq \forall R.\neg D \end{aligned}$$

- tell whether the TBox  $\mathcal{T}$  is satisfiable, and if so, show a model for  $\mathcal{T}$ ;
- tell whether the concept  $A$  is satisfiable with respect to  $\mathcal{T}$ , and if so, show a model for  $\mathcal{T}$  where the interpretation of  $A$  is non-empty;
- given the ABox  $\mathcal{A} = \{A(a)\}$ , tell whether the knowledge base  $\langle \mathcal{T}, \mathcal{A} \rangle$  entails the assertion  $\exists R.D(a)$ , explaining your answer;
- given the ABox  $\mathcal{A} = \{A \sqcap E(a)\}$ , tell whether the knowledge base  $\langle \mathcal{T}, \mathcal{A} \rangle$  is satisfiable (consistent), explaining your answer.

**Exercise 2** Given the following ASP program P:

```
r(x,y) :- p(y,x).
s(x,y) :- r(x,y).
s(x,z) :- r(x,y), r(y,z).
t(x,y) :- s(x,y), not r(x,y).
t(x,y) :- t(y,x).
v(x,y) :- t(x,y), not s(x,y).
w(x,z) :- v(x,y), not t(x,y).
p(a,b). p(b,c). p(c,d). p(e,f). p(f,g).
```

- tell whether P is stratified;
- compute the answer sets of P.

**Exercise 3**

We want to formalize knowledge about the domain of students and professors. In particular, we want to formalize the following statements:

- every student is a person;
  - every professor is a person;
  - active professor is a subclass of professor;
  - student and professor are disjoint classes;
  - the property “is friend of” has domain person and range person;
  - the property “is supervisor of” has domain professor and range student;
  - the property “studies with” has domain student and range student;
  - the property “studies with” is a subproperty of the property “is friend of”;
  - every professor that is the supervisor of at least one student is an active professor.
- Choose the most appropriate knowledge representation language for expressing the above knowledge among the following:  $\mathcal{ALC}$ , Datalog, ASP, OWL,  $DL\text{-}Lite_R$ ,  $\mathcal{EL}$ ,  $RL$ , RDFS, motivating your choice;
  - express the above knowledge in the formalism chosen at the previous point.

**Exercise 4**

- Write an RDF/RDFS model representing the following statements about URIs `Person`, `Director`, `Actor`, `Writer`, `Movie`, `Country`, `Comedy`, `Drama`, `Man`, `Woman`, `filmedIn`, `hasBoxOfficeGross`, `isDirectorOf`, `isWriterOf`, `actsIn`, `bornIn`, `Joe`, `Mary`, `Ann`, `Paul`, `Italy`, `France`, `ABC`, `XYZ`.
  - `Person`, `Director`, `Writer`, `Actor`, `Country`, `Movie`, `Comedy`, `Drama`, `Man`, and `Woman` are classes;
  - `Man` and `Woman` are subclasses of `Person`;
  - `Comedy` and `Drama` are subclasses of `Movie`;
  - `actsIn`, `bornIn`, `filmedIn`, `isDirectorOf` and `isWriterOf` are properties;

5. `isDirectorOf` has domain `Director` and range `Movie`;
  6. `filmedIn` has domain `Movie` and range `Country`;
  7. `bornIn` has domain `Person` and range `Country`;
  8. `actsIn` has domain `Actor` and range `Movie`;
  9. `hasBoxOfficeGross` has domain `Movie` and range `xsd:integer`;
  10. Ann is the director and the writer of movie XYZ;
  11. Joe and Paul act in movie ABC;
  12. ABC was filmed in France;
  13. Ann is a woman;
  14. Paul is a man.
- (b) Write SPARQL queries corresponding to the following requests: (b1) “return every movie filmed in the U.S.A. whose box office gross is above \$10,000,000 and, optionally, the country where the director of the movie was born in”; (b2) “return all the pairs of movies having the same director and such that at least one actor acts in both movies”.

### Exercise 5

- (a) Write an OWL ontology that formalizes the domain described at point (a) of Exercise 4.
- (b) Add to the above ontology the axioms formalizing the following statements:
1. add a new property `isWrittenBy` and state that it is the inverse of `isWriterOf`;
  2. add a new class `WrittenByMultipleAuthors` and state that it corresponds to the class of movies written by at least two writers;
  3. add a new class `hasLargeCast` and state that it corresponds to the class of movies played by at least 10 actors;
  4. add the new class `allFemaleCast` and state that such a class corresponds to the class consisting of every movie whose writers, directors and actors are all women;
  5. `bornIn` and `actsIn` are disjoint properties.

Then, tell whether the resulting OWL ontology is redundant, i.e.: can some of the axioms constituting the ontology be deleted without changing the meaning (that is, the models) of the ontology? if so, identify and list such axioms.

### Exercise 6

- (a) Axiomatize the following scenario, appropriately with action precondition and effect axioms, and obtain successor state axioms.

Fluents:

- `robotInsideRoom(s)` - The robot is inside the room in situation `s`.
- `windowOpen(s)` - The window is open in situation `s`.
- `robotCloseToWindow(s)` - The robot is close to the window in situation `s`.

Actions:

- `goInsideRoom` - The robot goes inside the room. This can be done if the robot is not inside the room, and has the effect that the robot will be inside the room.
- `goOutsideRoom` - The robot goes outside the room. This can be done if the robot is inside the room and the window is open, and has the effect that the robot will be outside the room.
- `goCloseToWindow` - The robot moves close to the window. This can be done if the robot is not close to the window and is inside the room, and has the effect that the robot will be close to the window.
- `openWindow` - The robot opens the window. This can be done if the robot is close to the window and the window is not open, and has the effect that the window will be open.

Initial situation description: Initially the robot is outside the room, is not close to the window, and the window is closed.

- (b) Show, by applying regression, that the window is open after the sequence of actions `goInsideRoom`, `goCloseToWindow`, `openWindow`, `goOutsideRoom`, and that the sequence of actions is indeed executable.